

7k Pump Trailer

Description

The adequate supply and management of water resources are critical to the success of any firefighting emergency response effort. Whether drafting from natural water sources or feeding off a facility's positive pressure water system, relaying water over miles of hose can be challenging.

The US Fire Pump Portable Boost Pump product line is a customizable, high-performance offering with multiple pump size options. Field-proven, these workhorse pumps have demonstrated they are built to run tirelessly, sustain high pressure, and deliver the large water volumes required for the most challenging industrial firefighting scenarios and water movement needs globally. Pumps are also available in Bronze and Stainless Steel for use in moving potable water during catastrophes and natural disasters.

US Fire Pump Portable Pumps incorporate a diesel driven proprietary centrifugal pump and utilize a premium diesel driver. Rugged corrosion-resistant designs, including full stainless-steel manifolds and produce an ideal system for draft and relay pump operations with fresh water, sea water, or brackish water.

Features

Global Emissions Compliance: US Fire Pump offers global emissions compliance with Tier II, III, and IV drivers.

Reliable Proven Track Record: These pump packages have been deployed by the US Fire Pump Emergency Response Team in their extensive, global response efforts. Boost Pump configurations are a critical component of our Emergency Response and Equipment Rental services.

Ease of Use and Serviceability: These packages offer a user-friendly operations interface, as well as low maintenance requirements. Typical field maintenance issues, such as fuel, oil, and filters, are minimal. Service partners are available globally for driver or service pump needs.

Designed for Mobility: Compatible with various transportation modes, these pumps provide a great deal of power in a portable package. They offer mobility and stability for deployment into any land or marine based exercise.

Wide Range of Available Options: Meet today's most challenging water movement scenarios with a fully customizable pump package tailored to your unique specifications.

NOTICE Although the information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of the date hereof, US FIRE PUMP and its affiliates makes no representations or warranties as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will US FIRE PUMP be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information or the product to which the information refers. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment or formulation in conflict with any patent, and US FIRE PUMP makes no representation or warranty, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.



Optional Features

- 12 V electric over hydraulic front and rear jacks (trailer mounted only)
- Suction and supply hose racks
- Toolbox(s)
- Hydraulic actuation clutch kit for ease of operation
- Dry Prime® Automatic Priming System
- Sound attenuated pump enclosure
- Collapsible awning over operator area
- Configurable with bumper-pull or gooseneck-styled trailer, or hook-lift/hook-arm skid configurations
- Open or closed configurations available
- Scene lighting

Note: Contact US Fire Pump Sales Department for additional custom configurations

FOR MORE INFORMATION VISIT WWW.USFIREPUMP.COM

US FIRE PUMP COMPANY, LLC
27995 James Chapel Road North, Holden, LA 70744
MAILING: PO Box 1810, Albany, LA 70711

EMERGENCY 24 HOUR RESPONSE: (225) 209-6551



USFP-202503-6

Technical Specifications

Standard Boost Pump Features	
Base Material	Carbon Steel
Unit Gross Weight (with fuel) ¹	13,500 lbs. (6123kg)
Pump Model	CVP-7000_10x12
Pump Type	Centrifugal End Suction
Pump Material	Standard option is Cast Iron, also available in Bronze and Stainless Steel
Drivers Available	CATERPILLAR, SCANIA, PERKINS
Fuel Cell Capacity	240 gallons standard. Fuel cell sized proportionately to the engine size and hourly consumption.
Standard Suction Inlets ²	(2) 12" Storz with caps, (4) 8" inlets with caps, (4) 2.5" FMNST with caps. Other options available.
Standard Discharge Outlets ²	(1) 12" outlets with control valves, (5) 6" outlets with control valves (4) 2.5" MNST with caps. Other options available.
Control Panel	Digital control panel and automatic pressure governors are used, offering full-functional output monitoring. Remote operation control are optional.
Light Packages	12V and 24V (as required) LED lighting mounted to interior and exterior positions provides full lighting capabilities for safe operations in and around the pump skid.
Unit Dimensions (LxWxH)	278x102x136" (706x 260x345cm)

Environmental and Safety Features	
Maximum Ambient Temperature	140° F (60° C) ⁴
Protection System	Emergency Kill Switch (select models), Master Power Disconnect, Air Intake AMOT Valve (Optional)
Standard Items Included (unless otherwise specified)	All inlet manifolds also include (3) each 2 1/2 in. style ball valve auxiliary inlets and 1 in. x 3 in. blind flange for optional equipment
	All discharge manifolds also include 2 each 2 1/2 in. app style ball valve auxiliary discharge outlets and 1 in. x 3 in. blind flange for optional equipment.
	Suction Hoses
	Floating Strainers

	7000 GPM capacity
Maximum run time with full fuel tank	8 hours per tank of fuel
Flow rate with 10ft (3.05m) suction lift	100 psi (6.9 bar) Net: 7,000gpm (26,500 Lpm)
	150 psi (10.3 bar) Net: 4,900 gpm (19,875 Lpm)
	200 psi (13.8 bar) Net: 3,500 gpm (13,250 Lpm)

- Notes:**
1. Only applies to standard units. May change with options.
 2. Customized units are available upon request.
 3. 6 ft. (1.8 m) lift.
 4. Options available for severe ambient temperatures.

Note: The converted metric values in this document are provided for dimensional reference only and do not reflect an actual measurement.

Note: US EPA Tier II, Tier III, and Tier IV Emissions Compliance available as required by region.

FOR MORE INFORMATION VISIT WWW.USFIREPUMP.COM

US FIRE PUMP COMPANY, LLC
 27995 James Chapel Road North, Holden, LA 70744
 MAILING: PO Box 1810, Albany, LA 70711

EMERGENCY 24 HOUR RESPONSE: (225) 209-6551



USFP-202503-6